

CLAIM AMENDMENTS

1 1. (Currently Amended) System for a sleeve-type packag-
2 ing machine, which wraps pieces (2) of packaging material around
3 articles (1), in which the said packaging machine comprises:

4 first article conveyor means (10), for feeding the
5 articles (1) longitudinally in sequence and spaced apart from each
6 other;

7 second article conveyor means (20), located downstream
8 and at a small distance from the said first article conveyor means
9 (10), thus creating a first opening (A1) between said first (10)
10 and said second (20) article conveyor means, the second article
11 conveyor means being able to receive the articles arriving from
12 said first article conveyor means (10) and to carry said articles
13 (1) along a wrapping plane which has an entry end and an exit end;

14 third article conveyor means (30), located downstream and
15 at a small distance from the said second article conveyor means
16 (20), thus creating a second opening (A2) between said second (20)
17 and the said third (30) article conveyor means, the third article
18 conveyor means, the third article conveyor means being able to
19 receive the articles (1) arriving from said second article conveyor
20 means (20);

21 means (40) for wrapping the pieces of sheet, located in
22 the proximity of said second article conveyor means (20), and
23 comprising at least one suspended wrapping bar (41), orientated
24 transversely with respect to the direction of advance of the
25 articles (1), and made to move through said first (A1) and said
26 second (A2) opening along an orbital path passing over the top of
27 the said second article conveyor means (20), the bar being capable
28 of carrying the pieces (2) of wrapping material;

29 piece conveyor means (50) with a conveyor belt (51),
30 positioned longitudinally below and in alignment in the proximity
31 of said first opening (A1), for feeding the pieces (2) of packaging
32 material in the proximity of the said first opening (A1); [[and]]

33 control means (70); ~~comprising~~ a first modular unit
34 (T100-G100) which is located under the article conveyor means (10)
35 and is movable and positionable with respect to the packaging
36 machine, for forming and feeding pieces (S 1) of packaging mate-
37 rial, said first modular unit being functionally connected to the
38 control means unit (70);

39 a second modular unit (T200-G200) which is located under
40 the first article conveyor means (10) and is movable and
41 positionable with respect to the packaging machine, for forming and
42 feeding pieces (S2) of packaging material, said second modular unit
43 being functionally connected to the control means (70);

44 and said first modular unit (T100-G100) and said second
45 modular unit (T200-G200) assume at least two positions, namely a

46 first position in which the modular unit (T100-T100; T200-G200) is
47 positioned at least transversely at the side of the packaging
48 machine, and a second position, in which the modular unit
49 (T100-G100; T200-G200) is positioned under the packaging machine in
50 order to feed the pieces (S1, S2) towards and above the conveyor
51 belt (51) of the piece conveyor means (50).

1 2. (Presently Presented) System according to claim 1,
2 characterized in that the said first modular unit (T100-G100)
3 comprise a frame with lateral plates (101a-101b) which are
4 parallel, interconnected and spaced apart from each other, and the
5 following components are supported between the said plates
6 (101a-101b):

7 support means (110) for supporting a reel (B100) of
8 packaging sheet (N 1);

9 first sensor means (120) for detecting when the reel
10 (B100) has been used up;

11 unwinding means (130) for unwinding the sheet (N 1) wound
12 on the reel (B 100), cutting means (140) for cutting the sheet (N
13 1), and feed means (150) for feeding the pieces (S 1) towards and
14 above the conveyor belt (51).

1 3. (Previously Presented) System according to claim 1,
2 characterized in that the said second modular unit (T200-G200)
3 comprise a frame with lateral plates (201a-201b) which are paral-

4 1el, interconnected and spaced apart from each other, and in that
5 the following components are supported between the said plates (201
6 a-201 b):

7 support means (210) for supporting a reel (B200) of
8 packaging sheet (N2);

9 first sensor means (220) for detecting when the reel
10 (B200) has been used up;

11 unwinding means (230) for unwinding the sheet (N2) wound
12 on the reel (B200), cutting means (240) for cutting the sheet (N2),
13 and feed means (250) for feeding the pieces (S2) towards and above
14 the conveyor belt (51).

1 4. (Previously Presented) System according to claim 1,
2 characterized in that additional second sensor means (53) are
3 provided along the transport branch of the piece conveyor means
4 (50) for detecting the front and rear edges of the pieces (S 1; S2)
5 being fed towards the said first opening (A1), and said second
6 sensor means (53) are connected to the control means (70).

1 5. (Previously Presented) 5. System according claim 1,
2 characterized in that the said control means (70) are able to
3 modify the motion of the said piece conveyor means (50) with
4 respect to the motion of the article conveyor means (10, 20, 30) in
5 order to produce the correct synchronization between the said

6 pieces (S1; S2) being moved towards the said first opening (A1) and
7 the articles (1) being moved towards the same first opening (A1).

1 6. System according to claim 5, characterized in that
2 the said piece conveyor means (50) are driven by a corresponding
3 servo motor (M50) connected to the control means (70) and said
4 control means (70) are able to modify the speed of the said servo
5 motor (M50) of the conveyor means (50).

1 7. (Previously Presented) System according to claim
2 2, characterized in that the said control means (70) modify the
3 speed of the unwinding means (130; 230) and the speed of the feed
4 means (150; 250) with respect to the speed of the piece conveyor
5 means (50).

1 8. (Previously Presented) System according to Claim 7,
2 characterized in that the unwinding means (130; 230) and the feed
3 means (150; 250) are driven by a corresponding servo motor (M100;
4 M200) connected to the control means (70) and said control means
5 (70) are able to modify the speed of the said servo motor (M100;
6 M200) of the unwinding means (130; 230) and of the feed means (150;
7 250).

1 9. (Previously Presented) System according to claim 2,
2 characterized in that the said first modular unit (T100-G100) and
3 the said second modular unit (T200-G200) include additional corre-
4 sponding third sensor means (170; 270) for detecting marks located
5 along the sheet (N1, N2), said third sensor means (170; 270) are
6 connected to the control means (70), said cutting means (140; 240)
7 are operated by an actuator (M140; M240) connected to and con-
8 trolled by the control means (70), and in that the said control
9 means (70) are able to drive the actuator (M140; M240) of the
10 cutting means (150; 250) in synchronization with the position
11 reached by the sheet (N1; N2) as detected by the aforesaid third
12 sensor means (170; 270), in order to cut the pieces in a specified
13 longitudinal position with respect to the said marks.

1 10. (Previously Presented) System according to claim 1,
2 characterized in that additional fourth sensor means (54) are
3 provided along the transport branch of the piece conveyor means
4 (50), for detecting marks located longitudinally along the pieces
5 (S 1; S2), said fourth sensor means (54) are connected to the
6 control means (70), and in that the said control means (70) are
7 able to modify the motion of the said piece conveyor means (50)
8 with respect to the motion of the article conveyor means (10, 20,
9 30) in order to produce the correct synchronization between the

10 said pieces (S 1; S2) being moved towards the said first opening
11 (A1) and the articles (1) being moved towards the same
12 10 first opening (A1).

1 11. (Previously Presented) System according to claim 1,
2 in which the fixed frame (1) of the packaging machine has two walls
3 (Fa, Fb), characterized in that it comprises in the said walls (Fa,
4 Fb) at least a first opening (B1, B2, B3, B4, B5) of sufficient
5 size to allow the free transverse sliding of the first modular unit
6 (T100-G100) and at least a second opening (C1, C2, C3, C4, C5) for
7 allowing the free transverse sliding of the second modular unit
8 (T200-G200).

9 12. (Previously Presented) System according to claim
10 1, characterized in that the said first modular unit
11 (T100-G100) and the said second modular unit (T200-G200) feed the
12 pieces (S1, S2) in two separate areas located respectively upstream
13 and downstream on the working branch of the conveyor belt (51) of
14 the piece conveyor means (50), for a change of reel from the first
15 modular unit (T100-G100) to the second modular unit
16 (T200-G200) the said second modular unit (T200-G200) is operated
17 for a specified period before stopping the first modular unit
18 (T100-G100), and for a change of reel from the second modular unit
19 (T200-G200) to the first modular unit (T100-G100) the said second
20 modular unit (T200-G200) is stopped and the first modular unit

(T100-G100) is operated after a specified period following this stop.

13. (Previously Presented) System according to claim 1, characterized in that a first modular unit (T100-G100) is positioned under the article conveyor means (10) with the branch (R100) for feeding the pieces (S 1) positioned at a first level and terminating in the proximity of the belt (51) of the piece conveyor means (50) and a second modular unit (T200-G200) is positioned under the said piece feeding branch (R100) of the first modular unit (T100-G100) with the branch (R200) for feeding the pieces (S2) positioned at a second level below the aforesaid branch (R100) and terminates in the proximity of the belt (51) of the piece conveyor means (50).

14. (Previously Presented) System according to claim 2, characterized in that the said first modular unit (T100-G100) and the said second modular unit (T200-G200) include additional respective fifth sensor means (160; 260) connected to the control means (70) for detecting the tension of the sheet (N1; N2) being unwound, said first modular unit (T100-G100) and the said second modular unit (T200-G200) include additional respective servo motors (M110, M210) for rotating the respective reels (B 100; B200), and said control means (70) use the said servo motors (M110, M210) of the reels (B100; B200) to control the rotation of the respective reels

11 (B100; B200) according to the signals received from the aforesaid
12 fifth sensor means (160; 260).

1 15. (Previously Presented) System according to claim 1,
2 characterized in that the said control means (70) include a
3 packaging cycle control program, the modular units (T100-G100;
4 T200-G200) are dissociated functionally from the packaging cycle
5 control program, and after this dissociation the various working
6 elements (110, M110, 130, 140, M140, 150, M100; 210, M210, 230,
7 240, M240, 250, M200) of the dissociated modular unit (T100-G100;
8 T200-G200) are operated singly and independently.

1 16. (Previously Presented) System according to claim 1,
2 characterized in that the said control means (70) include a first
3 packaging cycle control program and a second piece forming control
4 program, said second piece forming program can run independently of
5 the first packaging cycle control program, in that the modular
6 units (T100-G100; T200-G200) are dissociated functionally from the
7 first packaging cycle control program, and after this dissociation
8 the said second piece forming program is designed to operate and
9 control the working elements (110, M110, 120, 130, 140, M140, 150,
10 M100, 160; 210, M210, 220, 230, 240, M240, 250, M200, 260) of the
11 first or the second dissociated modular unit (T100-G100 or
12 T200-G200) in order to form and feed pieces (S 1 or S2).

17. (Previously Presented) System according to Claim 16, characterized in that the said second piece forming control program is used to enter new parameters for changing the format of the pieces which are to be produced.

18. (Previously Presented) System according to claim 1, characterized in that the said control means (70) include a packaging cycle control program, said first modular unit (T100-G100) or the said second modular unit (T200-G200) for forming and feeding the pieces (S1; S2) additionally includes respective servo motors (M110, M210) for rotating the respective reel (B100; B200), and during the change of reel the packaging cycle control program rotates the new reel (B 100; B200) by activating the corresponding servo motor (M1 10; M210) of the reels (B 100; B200).

19. (Previously Presented) System according to claim 1, characterized in that the said control means (70) include a packaging cycle control program, the said first modular unit (T100-100) or the said second modular unit (T200-G200) for forming and feeding the pieces (S1; S2) additionally includes respective servo motor (M110, M210) for rotating the respective reel (B 100; B200), and during the change of reel the packaging cycle control program stops the corresponding used reel (B100; B200) by activating the corresponding servo motor (M110; M210) of the reels (B100; B200).

1 20. (Previously Presented) System according to claim 1,
2 characterized in that the said control means (70) include a packag-
3 ing cycle control program, said first modular unit (T100-G100) or
4 the said second modular unit (T200-G200) for forming and feeding
5 the pieces (S₁; S₂) additionally include respective sixth sensor
6 means (160; 260) for detecting the tension of the sheet (N₁; N₂)
7 being unwound, said sixth sensor means (160; 260) are connected to
8 the control means (70), said first modular unit (T 100-G 100) or
9 the said second modular unit (T200-G200) for forming and feeding
10 the pieces (S₁; S₂) additionally include respective servo motor
11 (M110, M210) for rotating the respective reel (B 100; B200), and
12 said packaging cycle control program controls the said servo motor
13 (M110; M210) of the reels (B 100; B200) in order to optimize the
14 unwinding of the sheet (N₁; N₂) from the corresponding reel (B 100;
15 B200).

1 21. (Previously Presented) System according to claim 1,
2 characterized in that the first modular unit (T100-G100) is fitted
3 with a first reel (B100) and a corresponding first sheet (N₁),
4 second modular unit (T200-G200) is fitted with a second reel (B200)
5 and a corresponding second sheet (N₂) which are different from the
6 first reel (B 100) and the first sheet (N₁), and a packaging cycle
7 control program is provided which operates the first and second

8 modular units (T100-G100, T200-G200) alternately, in such a way
9 that a specified sequence of different pieces (S1-S2-S1, etc., or S
10 1-S 1 -S2-Si-S1-S2, etc.) is formed on the conveyor belt (51) of
11 the piece conveyor means (50).

22. (Previously Presented) System according to claim 1,
2 characterized in that a first servo motor (M10), connected to and
3 controlled by the control means (70), for driving said article
4 conveyor means (10, 20, 30);

5 a second servo motor (M40), connected to and controlled
6 by the control means (70), for driving said wrapping means (40);

7 a third servo motor (M50), connected to and controlled by
8 the control means (70), for driving the said piece conveyor means
9 (50); and

10 a fourth and fifth servo motors (M100; M200), connected
11 to and controlled by the control means (70), for driving, respec-
12 tively the said first and the said second modular units (T100-G100;
13 T200-G200).